



SSANGYONG



Technical specifications Rexton G4 MY'2017

Engine	e-XDi220		
Driven wheels	RWD	4WD	

Engine	Fuel	-	Diesel
	Fuel system	-	High pressure common rail direct injection
	Volume	cc	2'157
	Bore x Stroke	mm	86.2 x 92.4
	Compression ratio	-	15.5:1
	Cylinders	-	4, in line

Performance	Max power	kW/rpm	133.1/4'000
		PS/rpm	181/4'000
	Max torque	Nm/rpm	400/1'400~2'800 (420/1'600~2'600)
	Max speed	km/h	185

Drivetrain	Driven wheels		Rear wheels	Part-time (4x4) with low-gear mode and lock	
	Transmission		Manual, 6+1 (Automatic, Mercedes-Benz, 7+2)		
	Suspension	front	-	Double wishbone system with coil springs. Stabilizer bar.	
		rear	-	Five-link with coil springs or Impact-absorbing 10-link (IRS). Stabilizer bar.	
	Steering		Power steering		
	Brakes	front	-	Disc brakes, ventilated, 320 mm x 28 mm	
		rear	-	Disc brakes, ventilated, 315 mm x 20 mm	
	Wheels		-	Alloy wheels, 7.0Jx17 or 7.5Jx18 or 8.0Jx20	
Tires		-	235/70R17 or 255/60R18 or 255/50R20		

Dimensions	Length		mm	4'850
	Width		mm	1'960
	Height		mm	1'825 (with roof rack)
	Wheelbase		mm	2'865
	Tread	front	mm	1'640
		rear	mm	1'640
	Overhang	front	mm	895
		rear	mm	1'090
	Min clearance	front	mm	213
		rear	mm	203 (IRS:224)
	Min turning radius		m	5.5
	Approach angle		deg	20.0
	Departure angle		deg	22.5
	Ramp angle		deg	20.7
Seats, including driver		Number	7	

Weight	Gross vehicle weight		kg	2'850	2'960
	Kerb weight		kg	2'020~2'092 (2'030~2'133)	2'120~2'192 (2'130~2,233)
	Gross trailer weight	Bracked	kg	2'700	2'700 (3'000)
		Unbracked	kg	750	

Fuel	Consumption	Extra urban	l/100km	6.5 (6.8)	6.7 (7.0)
		Urban	l/100km	9.8 (10.1)	10.0 (10.4)
		Combined	l/100km	7.7 (8.0)	7.9 (8.3)
	CO ₂ (combined)		g/km	203 (211)	208 (218)
	Tank volume		litres	70	
	Emission regulation		Euro 6		

Remark: Figures in parentheses apply to Automatic Transmission only;

